

Template previews | Developer Documentation

Template previews

Updated: Nov 4, 2025

Request parameters

Placeholder	Description	Example Value
<code><LANGUAGE></code> <i>Comma-separated list</i>	Optional. Comma-separated list of language and locale codes of language versions you want returned. If omitted, versions of all supported languages will be returned.	<code>en_US,es_ES</code>
<code><ADD_SECURITY_RECOMMENDATION></code> <i>Boolean</i>	Optional. Set to <code>true</code> if you want the security recommendation body string included in the response. If omitted, the security recommendation string will not be included.	<code>true</code>
<code><CODE_EXPIRATION_MINUTES></code> <i>Int64</i>	Optional. Set to an integer if you want the code expiration footer string included in the response. If omitted, the code expiration footer string will not be included. Value indicates number of minutes until code expires. Minimum <code>1</code> , maximum <code>90</code> .	<code>10</code>

Placeholder	Description	Example Value
<p data-bbox="113 170 284 197"><BUTTON_TYPES></p> <p data-bbox="108 203 472 230"><i>Comma-separated list of strings</i></p>	<p data-bbox="577 170 703 197">Required.</p> <p data-bbox="577 241 943 304">Comma-separated list of strings indicating button type.</p> <p data-bbox="577 344 1002 443">If included, the response will include the button text for each button in the response.</p> <p data-bbox="577 483 963 546">For authentication templates, this value must be <code>OTP</code>.</p>	<p data-bbox="1050 170 1098 197"><code>OTP</code></p>

Revision #4

Created 2026-04-01 14:29:19 UTC by New Admin

Updated 2026-04-06 17:49:43 UTC by New Admin