

# WhatsApp Business Account - Migration Intent Details API | Developer Documentation

## WhatsApp Business Account - Migration Intent Details API

Copy for LLM

[View as Markdown](#)

Version

API for retrieving WhatsApp Business Account migration intent details and status information. This endpoint allows solution partners to retrieve comprehensive information about their WhatsApp Business Account migration intents, including current status and migration details.

---

### GET /{Version}/{Migration-Intent-ID}

Retrieve comprehensive details about a WhatsApp Business Account migration intent, including its current status and migration information.

Use Cases:

- Monitor migration intent lifecycle and status changes
- Verify migration intent configuration and current state
- Check migration progress and completion status
- Retrieve migration intent details for business workflows

Rate Limiting:

Standard Graph API rate limits apply. Use appropriate retry logic with exponential backoff.

Caching:

Migration intent details can be cached for short periods, but status information may change frequently during migration processes. Implement appropriate cache invalidation strategies.

# Request Syntax

Try it

Select language

---

Select status code

---

Header Parameters

---

User-Agentstring

The user agent string identifying the client software making the request.

Authorizationstring·required

Bearer token for API authentication. This should be a valid access token obtained through the appropriate OAuth flow or system user token.

Path Parameters

---

Versionstring·required

Graph API version to use for this request. Determines the API behavior and available features.

Migration-Intent-IDstring·required

Your Migration Intent ID. This ID is provided when you create the migration intent and can be found through migration management APIs.

Query Parameters

---

fieldsstring

Comma-separated list of fields to include in the response. If not specified, default fields will be returned (id, status).

Available fields: id, status

Responses

---

Retrieve comprehensive details about a WhatsApp Business Account migration intent, including its current status and migration information.

Use Cases:

Monitor migration intent lifecycle and status changes

Verify migration intent configuration and current state

Check migration progress and completion status

Retrieve migration intent details for business workflows

Rate Limiting:

Standard Graph API rate limits apply. Use appropriate retry logic with exponential backoff.

Caching:

Migration intent details can be cached for short periods, but status information may change frequently during migration processes. Implement appropriate cache invalidation strategies.

200

Successfully retrieved migration intent details

Content Type: application/json  
Schema: WhatsAppBusinessAccountMigrationIntent  
Show child attributes

---

WhatsAppBusinessAccountMigrationIntent

---

idstring·required  
Unique identifier for the migration intent

---

statusWhatsAppBusinessAccountMigrationStatus·required  
Current status of the WhatsApp Business Account migration intent  
400  
Bad Request - Invalid parameters or malformed request  
Content Type: application/json  
Schema: GraphAPIError  
Show child attributes

---

GraphAPIError

---

errorobject·required  
Show child attributes

---

messagestring·required  
Human-readable error message

---

typestring·required  
Error category type

---

codeinteger·required  
Numeric error code

---

error\_subcodeinteger  
More specific error subcode when available

---

fbtrace\_idstring  
Unique identifier for debugging and support requests with Meta

---

is\_transientboolean  
Indicates whether this error is temporary and the request should be retried

---

error\_user\_titlestring  
User-friendly error title for display purposes

---

error\_user\_msgstring  
User-friendly error message for display purposes  
401  
Unauthorized - Invalid or missing access token  
Content Type: application/json  
Schema: GraphAPIError  
Show child attributes

---

GraphAPIError

---

errorobject.required  
Show child attributes

---

messagestring.required  
Human-readable error message

---

typestring.required  
Error category type

---

codeinteger.required  
Numeric error code

---

error\_subcodeinteger  
More specific error subcode when available

---

fbtrace\_idstring  
Unique identifier for debugging and support requests with Meta

---

is\_transientboolean  
Indicates whether this error is temporary and the request should be retried

---

error\_user\_titlestring  
User-friendly error title for display purposes

---

error\_user\_msgstring  
User-friendly error message for display purposes  
403  
Forbidden - Insufficient permissions or access denied

Content Type: application/json

Schema: GraphAPIError

Show child attributes

---

GraphAPIError

---

errorobject·required

Show child attributes

---

messagestring·required

Human-readable error message

---

typestring·required

Error category type

---

codeinteger·required

Numeric error code

---

error\_subcodeinteger

More specific error subcode when available

---

fbtrace\_idstring

Unique identifier for debugging and support requests with Meta

---

is\_transientboolean

Indicates whether this error is temporary and the request should be retried

---

error\_user\_titlestring

User-friendly error title for display purposes

---

error\_user\_msgstring

User-friendly error message for display purposes

404

Not Found - Migration Intent ID does not exist or is not accessible

Content Type: application/json

Schema: GraphAPIError

Show child attributes

---

GraphAPIError

---

errorobject·required  
Show child attributes

---

messagestring·required  
Human-readable error message

---

typestring·required  
Error category type

---

codeinteger·required  
Numeric error code

---

error\_subcodeinteger  
More specific error subcode when available

---

fbtrace\_idstring  
Unique identifier for debugging and support requests with Meta

---

is\_transientboolean  
Indicates whether this error is temporary and the request should be retried

---

error\_user\_titlestring  
User-friendly error title for display purposes

---

error\_user\_msgstring  
User-friendly error message for display purposes  
422  
Unprocessable Entity - Request parameters are valid but cannot be processed  
Content Type: application/json  
Schema: GraphAPIError  
Show child attributes

---

GraphAPIError

---

errorobject·required  
Show child attributes

---

messagestring·required  
Human-readable error message

---

typestring·required  
Error category type

---

codeinteger·required  
Numeric error code

---

error\_subcodeinteger  
More specific error subcode when available

---

fbtrace\_idstring  
Unique identifier for debugging and support requests with Meta

---

is\_transientboolean  
Indicates whether this error is temporary and the request should be retried

---

error\_user\_titlestring  
User-friendly error title for display purposes

---

error\_user\_msgstring  
User-friendly error message for display purposes  
429  
Too Many Requests - Rate limit exceeded  
Content Type: application/json  
Schema: GraphAPIError  
Show child attributes

---

GraphAPIError

---

errorobject·required  
Show child attributes

---

messagestring·required  
Human-readable error message

---

typestring·required  
Error category type

---

codeinteger·required  
Numeric error code

---

error\_subcodeinteger

More specific error subcode when available

---

fbtrace\_idstring

Unique identifier for debugging and support requests with Meta

---

is\_transientboolean

Indicates whether this error is temporary and the request should be retried

---

error\_user\_titlestring

User-friendly error title for display purposes

---

error\_user\_msgstring

User-friendly error message for display purposes

500

Internal Server Error - Unexpected server error

Content Type: application/json

Schema: GraphAPIError

Show child attributes

---

GraphAPIError

---

errorobject.required

Show child attributes

---

messagestring.required

Human-readable error message

---

typestring.required

Error category type

---

codeinteger.required

Numeric error code

---

error\_subcodeinteger

More specific error subcode when available

---

fbtrace\_idstring

Unique identifier for debugging and support requests with Meta

---

is\_transientboolean

Indicates whether this error is temporary and the request should be retried

---

error\_user\_titlestring

User-friendly error title for display purposes

---

error\_user\_msgstring

User-friendly error message for display purposes

Select language

---

Select status code

---

## Authentication

Scheme	Type	Location
bearerAuth	HTTP Bearer	Header: Authorization

## Usage Examples

bearerAuth:

Include Authorization: Bearer your-token-here in request headers

## Global Authentication Requirements

All endpoints require:

bearerAuth

---

Revision #5

Created 2026-04-01 15:37:47 UTC by New Admin

Updated 2026-04-06 17:52:27 UTC by New Admin