

WhatsApp Business Account Solutions List API | Developer Documentation

WhatsApp Business Account Solutions List API

Copy for LLM

[View as Markdown](#)

Version

API for retrieving Multi-Partner Solutions associated with a WhatsApp Business Account (WABA). This endpoint allows authorized applications to retrieve a list of Multi-Partner Solutions that are associated with a specific WhatsApp Business Account.

GET `/{Version}/{WABA-ID}/solutions`

Retrieve a paginated list of Multi-Partner Solutions associated with the specified WhatsApp Business Account. This endpoint supports field selection and cursor-based pagination for efficient data retrieval.

Use Cases:

Discover available Multi-Partner Solutions for business onboarding

Monitor solution status and availability across your WABA

Retrieve solution ownership and permission details

Filter solutions by specific fields or status requirements

Rate Limiting:

Standard Graph API rate limits apply. Use appropriate retry logic with exponential backoff.

Caching:

Solution listings can be cached for short periods, but status information may change frequently during transitions. Implement appropriate cache invalidation strategies.

Pagination:

This endpoint supports cursor-based pagination using `limit`, `after`, and `before` parameters. Use the `paging` object in responses to navigate through result sets.

Request Syntax

Try it

Select language

Select status code

Header Parameters

User-Agentstring

The user agent string identifying the client software making the request.

Authorizationstring·required

Bearer token for API authentication. This should be a valid access token obtained through the appropriate OAuth flow or system user token.

Path Parameters

Versionstring·required

Graph API version to use for this request. Determines the API behavior and available features.

WABA-IDstring·required

WhatsApp Business Account ID for which to retrieve associated Multi-Partner Solutions.

This ID can be found in your WhatsApp Business Manager or through WABA management APIs.

Query Parameters

fieldsstring

Comma-separated list of fields to include in the response. If not specified, default fields will be returned (`name`, `status`, `status_for_pending_request`).

Available fields: `id`, `name`, `status`, `status_for_pending_request`, `owner_app`, `owner_permissions`

limitinteger [min: 1, max: 100]

Maximum number of solutions to return per page. Default is 25, maximum is 100.

afterstring

Cursor for pagination. Returns solutions after this cursor position.

Use the cursor from the previous response's `paging.cursors.after` field.

beforestring

Cursor for pagination. Returns solutions before this cursor position.

Use the cursor from the previous response's `paging.cursors.before` field.

Responses

Retrieve a paginated list of Multi-Partner Solutions associated with the specified WhatsApp Business Account. This endpoint supports field selection and cursor-based pagination for efficient data retrieval.

Use Cases:

Discover available Multi-Partner Solutions for business onboarding

Monitor solution status and availability across your WABA

Retrieve solution ownership and permission details

Filter solutions by specific fields or status requirements

Rate Limiting:

Standard Graph API rate limits apply. Use appropriate retry logic with exponential backoff.

Caching:

Solution listings can be cached for short periods, but status information may change frequently during transitions. Implement appropriate cache invalidation strategies.

Pagination:

This endpoint supports cursor-based pagination using `limit`, `after`, and `before` parameters. Use the `paging` object in responses to navigate through result sets.

200

Successfully retrieved Multi-Partner Solutions list

Content Type: application/json

Schema: SolutionsList

Show child attributes

SolutionsList

dataarray of WhatsAppBusinessSolution·required

Array of Multi-Partner Solutions associated with the WABA

Show child attributes

data[]WhatsAppBusinessSolution

Multi-Partner Solution details and configuration

Show child attributes

idstring·required

Unique identifier for the Multi-Partner Solution

namestring·required

Human-readable name of the Multi-Partner Solution

statusWhatsAppBusinessSolutionStatus·required

Current effective status of the Multi-Partner Solution

Show child attributes

status_for_pending_requestWhatsAppBusinessSolutionPendingStatus·required

Status of any pending solution status transition requests

owner_appApplicationNode
Meta application that owns the Multi-Partner Solution
Show child attributes

idstring
Unique identifier for the Meta application

namestring
Name of the Meta application

owner_permissionsarray of WhatsAppBusinessAccountPermissionTask
List of WhatsApp Business Account permissions granted to the solution owner
Show child attributes

owner_permissions[]WhatsAppBusinessAccountPermissionTask
Granular permission tasks for WhatsApp Business Account access

pagingPaging
Pagination information for cursor-based pagination
Show child attributes

cursorobject
Show child attributes

beforestring
Cursor pointing to the start of the page of data that has been returned

afterstring
Cursor pointing to the end of the page of data that has been returned

previousstring
Graph API endpoint URL for the previous page of data

nextstring
Graph API endpoint URL for the next page of data
400
Bad Request - Invalid parameters or malformed request
Content Type: application/json
Schema: GraphAPIError
Show child attributes

GraphAPIError

errorobject·required
Show child attributes

messagestring·required
Human-readable error message

typestring·required
Error category type

codeinteger·required
Numeric error code

error_subcodeinteger
More specific error subcode when available

fbtrace_idstring
Unique identifier for debugging and support requests with Meta

is_transientboolean
Indicates whether this error is temporary and the request should be retried

error_user_titlestring
User-friendly error title for display purposes

error_user_msgstring
User-friendly error message for display purposes
401
Unauthorized - Invalid or missing access token
Content Type: application/json
Schema: GraphAPIError
Show child attributes

GraphAPIError

errorobject·required
Show child attributes

messagestring·required

Human-readable error message

typestring·required
Error category type

codeinteger·required
Numeric error code

error_subcodeinteger
More specific error subcode when available

fbtrace_idstring
Unique identifier for debugging and support requests with Meta

is_transientboolean
Indicates whether this error is temporary and the request should be retried

error_user_titlestring
User-friendly error title for display purposes

error_user_msgstring
User-friendly error message for display purposes
403
Forbidden - Insufficient permissions or access denied
Content Type: application/json
Schema: GraphAPIError
Show child attributes

GraphAPIError

errorobject·required
Show child attributes

messagestring·required
Human-readable error message

typestring·required
Error category type

codeinteger·required

Numeric error code

error_subcodeinteger

More specific error subcode when available

fbtrace_idstring

Unique identifier for debugging and support requests with Meta

is_transientboolean

Indicates whether this error is temporary and the request should be retried

error_user_titlestring

User-friendly error title for display purposes

error_user_msgstring

User-friendly error message for display purposes

404

Not Found - WABA ID does not exist or is not accessible

Content Type: application/json

Schema: GraphAPIError

Show child attributes

GraphAPIError

errorobject·required

Show child attributes

messagestring·required

Human-readable error message

typestring·required

Error category type

codeinteger·required

Numeric error code

error_subcodeinteger

More specific error subcode when available

fbtrace_idstring

Unique identifier for debugging and support requests with Meta

is_transientboolean

Indicates whether this error is temporary and the request should be retried

error_user_titlestring

User-friendly error title for display purposes

error_user_msgstring

User-friendly error message for display purposes

422

Unprocessable Entity - Request parameters are valid but cannot be processed

Content Type: application/json

Schema: GraphAPIError

Show child attributes

GraphAPIError

errorobject.required

Show child attributes

messagestring.required

Human-readable error message

typestring.required

Error category type

codeinteger.required

Numeric error code

error_subcodeinteger

More specific error subcode when available

fbtrace_idstring

Unique identifier for debugging and support requests with Meta

is_transientboolean

Indicates whether this error is temporary and the request should be retried

error_user_titlestring

User-friendly error title for display purposes

error_user_msgstring

User-friendly error message for display purposes

429

Too Many Requests - Rate limit exceeded

Content Type: application/json

Schema: GraphAPIError

Show child attributes

GraphAPIError

errorobject-required

Show child attributes

messagestring-required

Human-readable error message

typestring-required

Error category type

codeinteger-required

Numeric error code

error_subcodeinteger

More specific error subcode when available

fbtrace_idstring

Unique identifier for debugging and support requests with Meta

is_transientboolean

Indicates whether this error is temporary and the request should be retried

error_user_titlestring

User-friendly error title for display purposes

error_user_msgstring

User-friendly error message for display purposes

500

Internal Server Error - Unexpected server error

Content Type: application/json

Schema: GraphAPIError

Show child attributes

GraphAPIError

errorobject·required

Show child attributes

messagestring·required

Human-readable error message

typestring·required

Error category type

codeinteger·required

Numeric error code

error_subcodeinteger

More specific error subcode when available

fbtrace_idstring

Unique identifier for debugging and support requests with Meta

is_transientboolean

Indicates whether this error is temporary and the request should be retried

error_user_titlestring

User-friendly error title for display purposes

error_user_msgstring

User-friendly error message for display purposes

Select language

Select status code

Authentication

Scheme	Type	Location
bearerAuth	HTTP Bearer	Header: Authorization

Usage Examples

bearerAuth:

Include `Authorization: Bearer your-token-here` in request headers

Global Authentication Requirements

All endpoints require:

bearerAuth

Revision #4

Created 2026-04-01 15:37:43 UTC by New Admin

Updated 2026-04-05 18:51:34 UTC by New Admin