

WhatsApp Business Multi-Partner Solutions - Solution Accept API | Developer Documentation

WhatsApp Business Multi-Partner Solutions - Solution Accept API

Copy for LLM

[View as Markdown](#)

Version

API for accepting Multi-Partner Solution partnership invitations.

This endpoint allows partner applications to accept invitations to participate in Multi-Partner Solutions.

POST /{Version}/{Solution-ID}/accept

Accept an invitation to participate in a Multi-Partner Solution as a partner application. This endpoint transitions the partner's status from NOTIFICATION_SENT to ACCEPTED, enabling the solution to progress toward ACTIVE status once all required partners accept.

Use Cases:

Accept partnership invitations for Multi-Partner Solutions

Activate partner participation in existing solutions

Confirm partner app's commitment to solution terms and conditions

Enable solution workflow progression from INITIATED to ACTIVE status

Business Logic:

Only invited partner apps can accept solution invitations

Solution must be in INITIATED status to accept partnerships
Partner status transitions from NOTIFICATION_SENT to ACCEPTED
Solution may become ACTIVE once all required partners accept
Acceptance creates formal partnership agreement between apps

Rate Limiting:

Standard Graph API rate limits apply. Use appropriate retry logic with exponential backoff.

Validation:

Partner app must have received a valid solution invitation
Solution must exist and be accessible to the partner app
Partner app must have proper permissions and capabilities
Acceptance request must include valid partner app identification

Request Syntax

Try it

Select language

Select status code

Header Parameters

User-Agentstring

The user agent string identifying the client software making the request.

Authorizationstring·required

Bearer token for API authentication. This should be a valid access token obtained through the appropriate OAuth flow or system user token.

Path Parameters

Versionstring·required

Graph API version to use for this request. Determines the API behavior and available features.

Solution-IDstring·required

ID of the Multi-Partner Solution to accept. This ID is provided in the original invitation and can be found in partner notifications or solution management interfaces.

Required

Content Type: application/json

Schema: WhatsAppBusinessSolutionAcceptRequest

Show child attributes

WhatsAppBusinessSolutionAcceptRequest

partner_app_idstring·required

ID of the partner application accepting the solution invitation.

This must match the app ID that received the original invitation.

log_session_idstring

Optional session identifier for logging and debugging purposes.

Used to track the acceptance flow across multiple API calls.

Responses

Accept an invitation to participate in a Multi-Partner Solution as a partner application. This endpoint transitions the partner's status from NOTIFICATION_SENT to ACCEPTED, enabling the solution to progress toward ACTIVE status once all required partners accept.

Use Cases:

Accept partnership invitations for Multi-Partner Solutions

Activate partner participation in existing solutions

Confirm partner app's commitment to solution terms and conditions

Enable solution workflow progression from INITIATED to ACTIVE status

Business Logic:

Only invited partner apps can accept solution invitations

Solution must be in INITIATED status to accept partnerships

Partner status transitions from NOTIFICATION_SENT to ACCEPTED

Solution may become ACTIVE once all required partners accept

Acceptance creates formal partnership agreement between apps

Rate Limiting:

Standard Graph API rate limits apply. Use appropriate retry logic with exponential backoff.

Validation:

Partner app must have received a valid solution invitation

Solution must exist and be accessible to the partner app

Partner app must have proper permissions and capabilities

Acceptance request must include valid partner app identification

200

Multi-Partner Solution invitation accepted successfully. The partner's status has been updated to ACCEPTED and the solution may progress toward ACTIVE status.

Content Type: application/json

Schema: WhatsAppBusinessSolutionAcceptResponse

Show child attributes

WhatsAppBusinessSolutionAcceptResponse

solution_idstring·required

ID of the Multi-Partner Solution that was accepted

partner_statusWhatsAppBusinessSolutionPartnerStatus·required

Current status of the partner's participation in the Multi-Partner Solution

successboolean·required

Indicates whether the acceptance was successful

messagestring

Human-readable confirmation message

update_timestring (date-time)

Timestamp when the acceptance was processed

400

Bad Request - Invalid parameters or malformed request

Content Type: application/json

Schema: GraphAPIError

Show child attributes

GraphAPIError

errorobject.required

Show child attributes

messagestring.required

Human-readable error message

typestring.required

Error category type

codeinteger.required

Numeric error code

error_subcodeinteger

More specific error subcode when available

fbtrace_idstring

Unique identifier for debugging and support requests with Meta

is_transientboolean

Indicates whether this error is temporary and the request should be retried

error_user_titlestring

User-friendly error title for display purposes

error_user_msgstring

User-friendly error message for display purposes

401

Unauthorized - Invalid or missing access token

Content Type: application/json

Schema: GraphAPIError

Show child attributes

GraphAPIError

errorobject.required

Show child attributes

messagestring.required

Human-readable error message

typestring.required

Error category type

codeinteger.required

Numeric error code

error_subcodeinteger

More specific error subcode when available

fbtrace_idstring

Unique identifier for debugging and support requests with Meta

is_transientboolean

Indicates whether this error is temporary and the request should be retried

error_user_titlestring

User-friendly error title for display purposes

error_user_msgstring

User-friendly error message for display purposes

403

Forbidden - Insufficient permissions or not invited to solution

Content Type: application/json

Schema: GraphAPIError

Show child attributes

GraphAPIError

errorobject·required
Show child attributes

messagestring·required
Human-readable error message

typestring·required
Error category type

codeinteger·required
Numeric error code

error_subcodeinteger
More specific error subcode when available

fbtrace_idstring
Unique identifier for debugging and support requests with Meta

is_transientboolean
Indicates whether this error is temporary and the request should be retried

error_user_titlestring
User-friendly error title for display purposes

error_user_msgstring
User-friendly error message for display purposes
404
Not Found - Solution ID does not exist or is not accessible
Content Type: application/json
Schema: GraphAPIError
Show child attributes

GraphAPIError

errorobject·required
Show child attributes

messagestring·required

Human-readable error message

typestring-required
Error category type

codeinteger-required
Numeric error code

error_subcodeinteger
More specific error subcode when available

fbtrace_idstring
Unique identifier for debugging and support requests with Meta

is_transientboolean
Indicates whether this error is temporary and the request should be retried

error_user_titlestring
User-friendly error title for display purposes

error_user_msgstring
User-friendly error message for display purposes
422
Unprocessable Entity - Solution cannot be accepted in current state
Content Type: application/json
Schema: GraphAPIError
Show child attributes

GraphAPIError

errorobject-required
Show child attributes

messagestring-required
Human-readable error message

typestring-required
Error category type

codeinteger-required

Numeric error code

error_subcodeinteger

More specific error subcode when available

fbtrace_idstring

Unique identifier for debugging and support requests with Meta

is_transientboolean

Indicates whether this error is temporary and the request should be retried

error_user_titlestring

User-friendly error title for display purposes

error_user_msgstring

User-friendly error message for display purposes

429

Too Many Requests - Rate limit exceeded

Content Type: application/json

Schema: GraphAPIError

Show child attributes

GraphAPIError

errorobject.required

Show child attributes

messagestring.required

Human-readable error message

typestring.required

Error category type

codeinteger.required

Numeric error code

error_subcodeinteger

More specific error subcode when available

fbtrace_idstring

Unique identifier for debugging and support requests with Meta

is_transientboolean

Indicates whether this error is temporary and the request should be retried

error_user_titlestring

User-friendly error title for display purposes

error_user_msgstring

User-friendly error message for display purposes

500

Internal Server Error - Unexpected server error

Content Type: application/json

Schema: GraphAPIError

Show child attributes

GraphAPIError

errorobject.required

Show child attributes

messagestring.required

Human-readable error message

typestring.required

Error category type

codeinteger.required

Numeric error code

error_subcodeinteger

More specific error subcode when available

fbtrace_idstring

Unique identifier for debugging and support requests with Meta

is_transientboolean

Indicates whether this error is temporary and the request should be retried

error_user_titlestring

User-friendly error title for display purposes

error_user_msgstring

User-friendly error message for display purposes

Select language

Select status code

Authentication

Scheme	Type	Location
bearerAuth	HTTP Bearer	Header: Authorization

Usage Examples

bearerAuth:

Include `Authorization: Bearer your-token-here` in request headers

Global Authentication Requirements

All endpoints require:

bearerAuth

Revision #5

Created 2026-04-01 15:39:37 UTC by New Admin

Updated 2026-04-06 17:52:40 UTC by New Admin